

Mr. Chuck Divine
Inwood Office Furniture, Inc.
P.O. Box 646
Jasper, Indiana, 47547-0646

Re: **037-12407-00012**
First Administrative Amendment to
Part 70 037-6048-00012

Dear Mr. Divine:

Inwood Office Furniture, Inc. was issued a Part 70 operating permit T037-6048-00012 for a wood furniture manufacturing plant. A source modification application requesting preconstruction and operating approval was received on April 12, 2000. Pursuant to the provisions of 2-7-11 the permit is hereby administratively amended to incorporate the significant source modification 037-12168-00012 to their existing Part 70 permit T037-6048-00012 as follows:

(1) The following units have been added to the A.2 section:

(c) Second surface coating line consisting of:

- (1) One (1) SAP/NGR Booth, identified as 21/22, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filter and exhausting externally through stacks 2A and 2B.**
- (2) One (1) wash Coat Booth, identified as 23, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filter and exhausting externally through stack 2C.**
- (3) One (1) Stain Booth, identified as 25, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filters and exhausting externally through stack 2D.**
- (4) One (1) Sealer Booth, identified as 27, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filters and exhausting externally through stack 2F.**
- (5) One (1) First Topcoat Booth with one (1) flash tunnel, identified as 29, with a maximum rated capacity of 30 units per hour. Particulate emissions from the First Topcoat Booth are controlled by dry-filters and exhausting externally through stack 2H. The flash tunnel exhausts externally through stack 2I.**
- (6) One (1) Second Topcoat Booth with one (1) flash tunnel, identified as 30, with a maximum rated capacity of 30 units per hour. Particulate emissions from the Second Topcoat Booth are controlled by dry-filters and exhausting externally through stack 2J. The flash tunnel exhausts externally through stack 2K.**

- (7) Two (2) Drying Ovens identified as 26 and 31, with a maximum rated capacity of 1.0 million Btu per hour each, and exhausting externally through stacks 2E and 2L.**
 - (8) One (1) Drying Oven identified as 28, with a maximum rated capacity of 4.0 million Btu per hour, and exhausting externally through stacks 2G-1, 2G-2, and 2G-3.**
 - (d) One (1) Final Touch-up Sanding Booth identified as 32, with a maximum rated capacity of 7.5 tons of wood per hour, particulate emissions controlled by cartridge-filters and exhausting internally.**
- (2) The following units have been added to A.3:**
- One (1) Air Makeup Unit utilized for general building ventilation, identified 33, with a maximum rated capacity of 2.10 million Btu per hour, and exhausting externally.**
- Seven (7) Air Makeup Units, two (2) integrated with the SAP/NGR Booth and one (1) integrated with each of the other five (5) surface coating booths, with a maximum rated capacity of 1.5 million Btu per hour per unit, and exhausting internally into the booth.**

- (3) Section D.2 is revised to include the second coating line.

Facility Description [326 IAC 2-7-5(15)]

(a) The first line consisting of the following units:

Twelve (12) surface coating booths, identified as units 01- 012 with dry filters for control. Unit 01 exhausts to stack A; Unit 02 exhausts to stack B; Unit 03 exhausts to stack c; Unit 04 exhausts to stack D; Unit 05 exhausts to stack E; Unit 06 exhausts to stack F; Unit 07 exhausts to stack G; Unit 08 exhausts to stack H; Unit 09 exhausts to stack I; Unit 010 exhausts to stack j; Unit 011 exhausts to stack K; Unit 012 exhausts to stack L;

(b) The second line consisting of the following units:

- (1) One (1) SAP/NGR Booth, identified as 21/22, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filter and exhausting externally through stacks 2A and 2B.**
- (2) One (1) wash Coat Booth, identified as 23, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filter and exhausting externally through stack 2C.**
- (3) One (1) Stain Booth, identified as 25, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filters and exhausting externally through stack 2D.**
- (4) One (1) Sealer Booth, identified as 27, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filters and exhausting externally through stack 2F.**
- (5) One (1) First Topcoat Booth with one (1) flash tunnel, identified as 29, with a maximum rated capacity of 30 units per hour. Particulate emissions from the First Topcoat Booth are controlled by dry-filters and exhausting externally through stack 2H. The flash tunnel exhausts externally through stack 2I.**
- (6) One (1) Second Topcoat Booth with one (1) flash tunnel, identified as 30, with a maximum rated capacity of 30 units per hour. Particulate emissions from the Second Topcoat Booth are controlled by dry-filters and exhausting externally through stack 2J. The flash tunnel exhausts externally through stack 2K.**
- (7) Two (2) Drying Ovens identified as 26 and 31, with a maximum rated capacity of 1.0 million Btu per hour each, and exhausting externally through stacks 2E and 2L.**
- (8) One (1) Drying Oven identified as 28, with a maximum rated capacity of 4.0 million Btu per hour, and exhausting externally through stacks 2G-1, 2G-2, and 2G-3.**

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

- (4) Section D.3 is revised to include the following units:

Facility Description [326 IAC 2-7-5(15)]

One (1) natural gas boiler 013, with a maximum rating of 2.6 million Btu per hour. Emissions shall be exhausted at stack M.

One (1) Air Makeup Unit utilized for general building ventilation, identified 33, with a maximum rated capacity of 2.10 million Btu per hour, and exhausting externally.

Seven (7) Air Makeup Units, two (2) integrated with the SAP/NGR Booth and one (1) integrated with each of the other five (5) surface coating booths, with a maximum rated capacity of 1.5 million Btu per hour per unit, and exhausting internally into the booth.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

- (5) A new section, D.4, has been added

All other conditions of the permit shall remain unchanged and in effect.

For convenience, the source is being provided a copy of the entire Title V permit with the pages affected revised to show changes made to incorporate the new second surface coating line and Final Touchup Sanding booth.

This decision is subject to the Indiana Administrative Orders and Procedures Act - IC 4-21.5-3-5. If you have any questions on this matter, please contact David Howard, at (800) 451-6027, press 0 and ask for (David Howard) or extension (2-8422), or dial (317) 232-8422.

Sincerely,

Paul Dubenetzky, Chief
Permits Branch
Office of Air Management

Attachments

DWH

cc: File - Dubois County
U.S. EPA, Region V
Dubois County Health Department
SWRO
Air Compliance Section Inspector Gene Kelso
Compliance Data Section - Karen Nowak
Administrative and Development - Janet Mobley
Technical Support and Modeling - Michele Boner

PART 70 OPERATING PERMIT OFFICE OF AIR MANAGEMENT

**Inwood Office Furniture Co., Inc.
1108 E. 15th Street
Jasper, Indiana 47546**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 and 326 IAC 2-1-3.2 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments) 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T037-6048-00012	
Issued by: Janet G. McCabe, Assistant Commissioner Office of Air Management	Issuance Date: 12-21-98

Significant Permit Modification No.:037-10817-00012	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

Significant Source Modification: **037-12168-00012**

First Administrative Amendment: 037-12407-00012	Pages Affected: 6,30,36,37
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

TABLE OF CONTENTS

A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
- A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
- A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

B GENERAL CONDITIONS

- B.1 Permit No Defense [326 IAC 2-1-10][IC 13]
- B.2 Definitions [326 IAC 2-7-1]
- B.3 Permit Term [326 IAC 2-7-5(2)]
- B.4 Enforceability [326 IAC 2-7-7(a)]
- B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]
- B.6 Severability [326 IAC 2-7-5(5)]
- B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
- B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)]
- B.9 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]
- B.10 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)]
- B.11 Annual Compliance Certification [326 IAC 2-7-6(5)]
- B.12 Preventive Maintenance Plan [326 IAC 2-7-5] [326 IAC 2-7-6] [326 IAC 1-6-3]
- B.13 Emergency Provisions [326 IAC 2-7-16]
- B.14 Permit Shield [326 IAC 2-7-15]
- B.15 Multiple Exceedances [326 IAC 2-7-5(1)(E)]
- B.16 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]
- B.17 Permit Modification, Reopening, Revocation and Reissuance, or Termination
- B.18 Permit Renewal [326 IAC 2-7-4]
- B.19 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]
- B.20 Permit Revision Under Economic Incentives and Other Programs
- B.21 Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-7-20(b)]
- B.22 Operational Flexibility [326 IAC 2-7-20]
- B.23 Construction Permit Requirement [326 IAC 2]
- B.24 Inspection and Entry [326 IAC 2-7-6(2)]
- B.25 Transfer of Ownership or Operation [326 IAC 2-1-6] [326 IAC 2-7-11]
- B.26 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]

C SOURCE OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Matter Emission Limitations
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- C.4 Incineration [326 IAC 4-2][326 IAC 9-1-2]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- C.6 Operation of Equipment [326 IAC 2-7-6(6)]
- C.7 Stack Height [326 IAC 1-7]
- C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

Testing Requirements [326 IAC 2-7-6(1)]

- C.9 Performance Testing [326 IAC 3-6]

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

- C.10 Compliance Schedule [326 IAC 2-7-6(3)]
- C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

C.12 Monitoring Methods [326 IAC 3]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]
- C.15 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5]
- C.16 Actions Related to Noncompliance Demonstrated by a Stack Test

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.17 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-6][326 IAC 2-7-19]
- C.18 Monitoring Data Availability [326 IAC 2-7-6(1)][326 IAC 2-7-5(3)]
- C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)]
- C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

Stratospheric Ozone Protection

- C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

D.1 FACILITY OPERATION CONDITIONS- Woodworking Operations

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Nonattainment Area Particulate Matter (PM) Emission Limitations [326 IAC 6-1-2]
- D.1.2 Opacity
- D.1.3 Baghouse limitations
- D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.1.5 Testing Requirements [326 IAC 2-7-6(1), (6)]
- D.1.6 Opacity
- D.1.7 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.8 Visible Emissions Notations
- D.1.9 Baghouse Inspections
- D.1.10 Broken Bag or Failure Detection

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.11 Record Keeping Requirements

D.2 FACILITY OPERATION CONDITIONS- Surface Coating Booths

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.2.1 General Provisions Relating to HAPs [326 IAC 20-1-1][40 CFR 63, Subpart A]
- D.2.2 Nonattainment Area Particulate Matter (PM) Emission Limitations [326 IAC 6-1-2]
- D.2.3 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]
- D.2.4 Wood Furniture NESHAP [40 CFR 63, Subpart JJ]
- D.2.5 Preventive Maintenance Plan [326 IAC 2-7-5(13)]
- D.2.6 Work Practice Standards [40 CFR 63.803]

Compliance Determination Requirements

- D.2.7 Testing Requirements [326 IAC 2-7-6(1), (6)][40 CFR 63, Subpart JJ]
- D.2.8 Volatile Organic Compounds (VOC)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.2.9 Particulate Matter (PM)

D.2.10 Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.11 Record Keeping Requirements

D.2.12 Reporting Requirements

D.3 FACILITY OPERATION CONDITIONS - Natural Gas fired Boiler

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Nonattainment Area Particulate Matter (PM) Emission Limitations [326 IAC 6-1-2]

Compliance Determination Requirements

D.3.2 Testing Requirements [326 IAC 2-7-6(1), (6)]

D.4 FACILITY OPERATION CONDITIONS - Final Touchup Sanding Booth

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.4.1 Nonattainment Area Particulate Matter Emissions [326 IAC 6-1-2]

D.4.2 Opacity

D.4.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

D.4.4 Testing Requirements [326 IAC 2-7-6(1),(6)]

D.4.5 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.4.6 Visible Emissions Notations

D.4.7 Parametric Monitoring

D.4.8 Cartridge Filter Inspections

D.4.9 Broken Cartridge Filter of Failure Detection

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)][326 IAC 2-7-19]

D.4.10 Record Keeping Requirements

PART 70 PERMIT CERTIFICATION FORM

Emergency/Deviation Occurrence Report Form

Semi-Annual Report

Quarterly Compliance Monitoring Report

A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates a furniture manufacturing plant.

Responsible Official:	Glen M. Sturm
Source Address:	1108 E. 15th Street, Jasper, IN 47546
Mailing Address:	P.O. Box 646, Jasper, IN 47547-0646
SIC Code:	2521
County Location:	Dubois
County Status:	Nonattainment for total suspended particulate Attainment for all other criteria pollutants
Source Status:	Major Source under PSD Part 70 Permit Program Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

- (a) Woodworking operations 014, with a maximum rating of 2750 pounds per hour. Emissions shall be controlled by a baghouse, then exhausted at stack N.
- (b) Surface coating booths 01-012, consisting of the following:
 - (1) One (1) contact glue booth 01, with a maximum rating of 11.1 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack A.
 - (2) Three (3) stain booths 02-04, with a maximum rating of 3 units per hour each. Emissions shall be controlled by dry filters, then exhausted at stacks B, C and D.
 - (3) One (1) wipe stain booth 05, with a maximum rating of 10 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack E.
 - (4) One (1) sealer booth 06, with a maximum rating of 10 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack F.
 - (5) One (1) lacquer booth 07, with a maximum rating of 10 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack G.
 - (6) One (1) lacquer booth 08, with a maximum rating of 8 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack H.
 - (7) One (1) wipe stain booth 09, with a maximum rating of 1.1 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack I.

- (8) One (1) lacquer booth 010, with a maximum rating of 1.1 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack J.
 - (9) One (1) black enamel booth 011, with a maximum rating of 11.1 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack K.
 - (10) One (1) stain booth 012, with a maximum rating of 1.1 units per hour. Emissions shall be controlled by dry filters, then exhausted at stack L.
- (c) Second surface coating line consisting of:
- (1) One (1) SAP/NGR Booth, identified as 21/22, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filter and exhausting externally through stacks 2A and 2B.
 - (2) One (1) wash Coat Booth, identified as 23, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filter and exhausting externally through stack 2C.
 - (3) One (1) Stain Booth, identified as 25, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filters and exhausting externally through stack 2D.
 - (4) One (1) Sealer Booth, identified as 27, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filters and exhausting externally through stack 2F.
 - (5) One (1) First Topcoat Booth with one (1) flash tunnel, identified as 29, with a maximum rated capacity of 30 units per hour. Particulate emissions from the First Topcoat Booth are controlled by dry-filters and exhausting externally through stack 2H. The flash tunnel exhausts externally through stack 2I.
 - (6) One (1) Second Topcoat Booth with one (1) flash tunnel, identified as 30, with a maximum rated capacity of 30 units per hour. Particulate emissions from the Second Topcoat Booth are controlled by dry-filters and exhausting externally through stack 2J. The flash tunnel exhausts externally through stack 2K.
 - (7) Two (2) Drying Ovens identified as 26 and 31, with a maximum rated capacity of 1.0 million Btu per hour each, and exhausting externally through stacks 2E and 2L.
 - (8) One (1) Drying Oven identified as 28, with a maximum rated capacity of 4.0 million Btu per hour, and exhausting externally through stacks 2G-1, 2G-2, and 2G-3.
- (d) One (1) Final Touch-up Sanding Booth identified as 32, with a maximum rated capacity of 7.5 tons of wood per hour, particulate emissions controlled by cartridge-filters and exhausting internally.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)]
[326 IAC 2-7-5(15)]

This stationary source also includes the following insignificant activities which are specifically regulated, as defined in 326 IAC 2-7-1(21).

- (a) One (1) natural gas boiler 013, with a maximum rating of 2.6 million British thermal units (Btu) per hour. Emissions shall exhaust at stack M
- (b) One (1) Air Makeup Unit utilized for general building ventilation, identified 33, with a maximum rated capacity of 2.10 million Btu per hour, and exhausting externally.
- (c) Seven (7) Air Makeup Units, two (2) integrated with the SAP/NGR Booth and one (1) integrated with each of the other five (5) surface coating booths, with a maximum rated capacity of 1.5 million Btu per hour per unit, and exhausting internally into the booth.

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22).
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

B GENERAL CONDITIONS

B.1 Permit No Defense [326 IAC 2-1-10] [IC 13]

- (a) Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7.
- (b) This prohibition shall not apply to alleged violations of applicable requirements for which the Commissioner has granted a permit shield in accordance with 326 IAC 2-1-3.2 or 326 IAC 2-7-15, as set out in this permit in the Section B condition entitled "Permit Shield."

B.2 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, any applicable definitions found in IC 13-11, and 326 IAC 1-2, and 326 IAC 2-7 shall prevail.

B.3 Permit Term [326 IAC 2-7-5(2)]

This permit is issued for a fixed term of five (5) years from the effective date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3.

B.4 Enforceability [326 IAC 2-7-7(a)]

- (a) All terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM.
- (b) Unless otherwise stated, terms and conditions of this permit, including any provisions to limit the source's potential to emit, are enforceable by the United States Environmental Protection Agency (U.S. EPA) and citizens under the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.6 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)]

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The Permittee shall furnish to IDEM, OAM, within a reasonable time, any information that IDEM, OAM may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit.
- (c) Upon request, the Permittee shall also furnish to IDEM, OAM copies of records required to be kept by this permit. If the Permittee wishes to assert a claim of confidentiality over any of the furnished records, the Permittee must furnish such records to IDEM, OAM along with a claim of confidentiality under 326 IAC 17. If requested by IDEM, OAM, or the U.S. EPA, to furnish copies of requested records directly to U. S. EPA, and if the Permittee is making a claim of confidentiality regarding the furnished records, then the Permittee must furnish such confidential records directly to the U.S. EPA along with a claim of confidentiality under 40 CFR 2, Subpart B.

B.9 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit constitutes a violation of the Clean Air Act and is grounds for:
 - (1) Enforcement action;
 - (2) Permit termination, revocation and reissuance or modification; or for
 - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

B.10 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)]

- (a) Any application form, report, or compliance certification submitted under this permit shall contain certification by a responsible official of truth, accuracy, and completeness. This certification and any other certification required under this permit shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.11 Annual Compliance Certification [326 IAC 2-7-6(5)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The identification of each term and condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was based on continuous or intermittent data;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3);
 - (5) Any insignificant activity that has been added without a permit revision; and
 - (6) Such other facts, as specified in Sections D of this permit, as IDEM, OAM, may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.12 Preventive Maintenance Plan [326 IAC 2-7-5] [326 IAC 2-7-6] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMP) within ninety (90) days after issuance of this permit, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions;
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMP cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015

Indianapolis, Indiana 46206-6015

- (b) The Permittee shall implement the Preventive Maintenance Plans as necessary to ensure that lack of proper maintenance does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) PMP's shall be submitted to IDEM, OAM, upon request and shall be subject to review and approval by IDEM, OAM.

B.13 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-7-16.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- (3) During the period of emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAM, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Management, Compliance Section) or,
Telephone No.: 317-233-5674 (ask for Office of Air Management, Compliance Section)
Facsimile No.: 317-233-5967

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice, either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAM may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAM, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operation shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

B.14 Permit Shield [326 IAC 2-7-15]

- (a) This condition provides a permit shield as addressed in 326 IAC 2-7-15.
- (b) This permit shall be used as the primary document for determining compliance with applicable requirements established by previously issued permits. Compliance with the

conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that:

- (1) The applicable requirements are included and specifically identified in this permit;
or
- (2) The permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable.
- (c) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAM shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (d) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application.
- (e) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act; and
 - (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (f) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (g) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAM, has issued the modifications.[326 IAC 2-7-12(c)(7)]
- (h) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAM has issued the modification. [326 IAC 2-7-12(b)(8)]

B.15 Multiple Exceedances [326 IAC 2-7-5(1)(E)]

Any exceedance of a permit limitation or condition contained in this permit, which occurs contemporaneously with an exceedance of an associated surrogate or operating parameter established to detect or assure compliance with that limit or condition, both arising out of the same act or occurrence, shall constitute a single potential violation of this permit.

B.16 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within ten (10) calendar days from the date of the discovery of the deviation.

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:
- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
 - (2) An emergency as defined in 326 IAC 2-7-1(12); or
 - (3) Failure to implement elements of the Preventive Maintenance Plan unless lack of maintenance has caused or contributed to a deviation.
 - (4) Failure to make or record information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.
- A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.
- (c) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent. The notification does not need to be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirements of this subsection.

**B.17 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]**

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)]
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAM determines any of the following:
- (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.

- (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAM, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practical. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit under 326 IAC 2-7-9(a) shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAM, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAM, may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.18 Permit Renewal [326 IAC 2-7-4]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAM, and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due. [326 IAC 2-5-3]
 - (2) If IDEM, OAM, upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-7-3]
If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAM takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAM, any additional information identified as being needed to process the application.

- (d) United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)]
If IDEM, OAM fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.

B.19 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "responsible official" as defined by 326 IAC 2-7-1(34) only if a certification is required by the terms of the applicable rule.
- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.20 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (c) Notwithstanding 326 IAC 2-7-12(b)(1)(D)(i) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.21 Changes Under Section 502(b)(10) of the Clean Air Act [326 IAC 2-7-20(b)]

The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a) and the following additional conditions:

- (a) For each such change, the required written notification shall include a brief description of the change within the source, the date on which the change will occur, any change in emissions, and any permit term or condition that is no longer applicable as a result of the change.
- (b) The permit shield, described in 326 IAC 2-7-15, shall not apply to any change made under 326 IAC 2-7-20(b).

B.22 Operational Flexibility [326 IAC 2-7-20]

- (a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without prior permit revision, if each of the following conditions is met:
- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
 - (2) Any approval required by 326 IAC 2-1 has been obtained;
 - (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
 - (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and
 - (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20(b), (c), or (e), and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAM, in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1) and (e)(2).
- (b) For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
- (1) A brief description of the change within the source;
 - (2) The date on which the change will occur;
 - (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) Emission Trades [326 IAC 2-7-20(c)]
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).
- (d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAM or U.S. EPA is required.
- (e) Backup fuel switches specifically addressed in, and limited, under Section D of this permit shall not be considered alternative operating scenarios. Therefore, the notification requirements of part (a) of this condition do not apply.

B.23 Construction Permit Requirement [326 IAC 2]

Except as allowed by Indiana P.L. 130-1996 Section 12, as amended by P.L. 244-1997, modification, construction, or reconstruction shall be approved as required by and in accordance with 326 IAC 2.

B.24 Inspection and Entry [326 IAC 2-7-6(2)]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, the Permittee shall allow IDEM, OAM, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements. [326 IAC 2-7-6(6)]
 - (1) The Permittee may assert a claim that, in the opinion of the Permittee, information removed or about to be removed from the source by IDEM, OAM, or an authorized representative, contains information that is confidential under IC 5-14-3-4(a). The claim shall be made in writing before or at the time the information is removed from the source. In the event that a claim of confidentiality is so asserted, neither IDEM, OAM, nor an authorized representative, may disclose the information unless and until IDEM, OAM, makes a determination under 326 IAC 17-1-7 through 326 IAC 17-1-9 that the information is not entitled to confidential treatment and that determination

becomes final. [IC 5-14-3-4; IC 13-14-11-3; 326 IAC 17-1-7 through 326 IAC 17-1-9]

- (2) The Permittee, *and* IDEM, OAM, acknowledge that the federal law applies to claims of confidentiality made by the Permittee with regard to information removed or about to be removed from the source by U.S. EPA. [40 CFR Part 2, Subpart B]

B.25 Transfer of Ownership or Operation [326 IAC 2-1-6] [326 IAC 2-7-11]

Pursuant to 326 IAC 2-1-6 and 326 IAC 2-7-11:

- (a) In the event that ownership of this source is changed, the Permittee shall notify IDEM, OAM, Permits Branch, within thirty (30) days of the change. Notification shall include a written agreement containing a specific date for transfer of permit responsibility, coverage, and liability between the Permittee and the new owner.
- (b) The written notification shall be sufficient to transfer the permit to the new owner by an administrative amendment pursuant to 326 IAC 2-7-11. The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) IDEM, OAM shall reserve the right to issue a new permit.

B.26 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)]

- (a) The Permittee shall pay annual fees to IDEM, OAM, within thirty (30) calendar days of receipt of a billing. If the Permittee does not receive a bill from IDEM, OAM the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAM, Technical Support and Modeling Section), to determine the appropriate permit fee.

C SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

C.1 Particulate Matter Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [326 IAC 6-3-2(c)]

Pursuant to 326 IAC 6-3-2(c), the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of thirty percent (30%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3(a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2][326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Operation of Equipment [326 IAC 2-7-6(6)]

All air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.7 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

C.8 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3). All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) Procedures for Asbestos Emission Control: The Permittee shall comply with the emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are mandatory for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) Indiana Accredited Asbestos Inspector: The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.

Testing Requirements [326 IAC 2-7-6(1)]

C.9 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in the permit, utilizing methods approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The Permittee shall submit a notice of the actual test date to the above address so that it is received at least two weeks prior to the test date.

- (b) All test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by the Commissioner, if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

The documentation submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.10 Compliance Schedule [326 IAC 2-7-6(3)]

The Permittee:

- (a) Has certified that all facilities at this source are in compliance with all applicable requirements; and
- (b) Has submitted a statement that the Permittee will continue to comply with such requirements; and
- (c) Will continue to comply with such requirements that become effective during the term of this permit.

C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Compliance with applicable requirements shall be documented as required by this permit. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment, no more than ninety (90) days after receipt of this permit. If due to circumstances beyond its control, this schedule cannot be met, the Permittee may extend compliance schedule an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.12 Monitoring Methods [326 IAC 3]

Any monitoring or testing performed to meet the applicable requirements of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.13 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee shall prepare written emergency reduction plans (ERPs) consistent with safe operating procedures.

- (b) These ERPs shall be submitted for approval to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within ninety (90) days after the date of issuance of this permit.

The ERP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (c) If the ERP is disapproved by IDEM, OAM, the Permittee shall have an additional thirty (30) days to resolve the differences and submit an approvable ERP.
- (d) These ERPs shall state those actions that will be taken, when each episode level is declared, to reduce or eliminate emissions of the appropriate air pollutants.
- (e) Said ERPs shall also identify the sources of air pollutants, the approximate amount of reduction of the pollutants, and a brief description of the manner in which the reduction will be achieved.
- (f) Upon direct notification by IDEM, OAM, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level. [326 IAC 1-5-3]

C.14 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present in a process in more than the threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall:

- (a) Submit:

- (1) A compliance schedule for meeting the requirements of 40 CFR 68 by the date provided in 40 CFR 68.10(a); or

- (2) As a part of the compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and
- (3) A verification to IDEM, OAM, that a RMP or a revised plan was prepared and submitted as required by 40 CFR 68.
- (b) Provide annual certification to IDEM, OAM, that the Risk Management Plan is being properly implemented.

All documents submitted pursuant to this condition shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.15 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6] [326 IAC 1-6]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. This compliance monitoring plan is comprised of:
 - (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this permit;
 - (3) The Compliance Monitoring Requirements in Section D of this permit;
 - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
 - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of :
 - (A) Response steps that will be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and
 - (B) A time schedule for taking such response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, appropriate response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to perform the actions detailed in the compliance monitoring conditions or failure to take the response steps within the time prescribed in the Compliance Response Plan, shall constitute a violation of the permit unless taking the response steps set forth in the Compliance Response Plan would be unreasonable.

- (c) After investigating the reason for the excursion, the Permittee is excused from taking further response steps for any of the following reasons:
- (1) The monitoring equipment malfunctioned, giving a false reading. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied or;
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned to operating within "normal" parameters and no response steps are required.
- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.

C.16 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize emissions from the affected facility while the corrective actions are being implemented. IDEM, OAM shall notify the Permittee within thirty (30) days, if the corrective actions taken are deficient. The Permittee shall submit a description of additional corrective actions taken to IDEM, OAM within thirty (30) days of receipt of the notice of deficiency. IDEM, OAM reserves the authority to use enforcement activities to resolve noncompliant stack tests.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline. Failure of the second test to demonstrate compliance with the appropriate permit conditions may be grounds for immediate revocation of the permit to operate the affected facility.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.17 Emission Statement [326 IAC 2-7-5(3)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]

- (a) The Permittee shall submit an annual emission statement certified pursuant to the requirements of 326 IAC 2-6, that must be received by July 1 of each year and must comply with the minimum requirements specified in 326 IAC 2-6-4. This annual emission statement shall meet the following requirements:

- (1) Indicate actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
 - (2) Indicate actual emissions of other regulated pollutants from the source, for purpose of part 70 fee assessment.
- (b) The annual emission statement covers the twelve (12) consecutive month time period starting January 1 and ending December 31. The annual emission statement must be submitted to:
- Indiana Department of Environmental Management
Technical Support and Modeling Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015
- (c) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM on or before the date it is due.

C.18 Monitoring Data Availability [326 IAC 2-7-6(1)][326 IAC 2-7-5(3)]

- (a) With the exception of performance tests conducted in accordance with Section C-Performance Testing, all observations, sampling, maintenance procedures, and record keeping, required as a condition of this permit shall be performed at all times the equipment is operating at normal representative conditions.
- (b) As an alternative to the observations, sampling, maintenance procedures, and record keeping of subsection (a) above, when the equipment listed in Section D of this permit is not operating, the Permittee shall either record the fact that the equipment is shut down or perform the observations, sampling, maintenance procedures, and record keeping that would otherwise be required by this permit.
- (c) If the equipment is operating but abnormal conditions prevail, additional observations and sampling should be taken with a record made of the nature of the abnormality.
- (d) If for reasons beyond its control, the operator fails to make required observations, sampling, maintenance procedures, or record keeping, reasons for this must be recorded.
- (e) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent (5%) of the operating time in any quarter.
- (f) Temporary, unscheduled unavailability of staff qualified to perform the required observations, sampling, maintenance procedures, or record keeping shall be considered a valid reason for failure to perform the requirements stated in (a) above.

C.19 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years and available upon request of an IDEM, OAM, representative. The records may

be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a written request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

- (b) Records of required monitoring information shall include, where applicable:
 - (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
 - (1) Copies of all reports required by this permit;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance shall be sufficient to demonstrate that improper maintenance did not cause or contribute to a violation of any limitation on emissions or potential to emit. To be relied upon subsequent to any such violation, these records may include, but are not limited to: work orders, parts inventories, and operator's standard operating procedures. Records of response steps taken shall indicate whether the response steps were performed in accordance with the Compliance Response Plan required by Section C - Compliance Monitoring Plan - Failure to take Response Steps, of this permit, and whether a deviation from a permit condition was reported. All records shall briefly describe what maintenance and response steps were taken and indicate who performed the tasks.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.20 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

- (a) To affirm that the source has met all the compliance monitoring requirements stated in this permit, the source shall submit a Quarterly Compliance Monitoring Report. Any deviation from the requirements and the date(s) of each deviation must be reported.
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (d) Unless otherwise specified in this permit, any report shall be submitted within thirty (30) days of the end of the reporting period.
- (e) All instances of deviations as described in Section B - Deviations from Permit Requirements Conditions must be clearly identified in such reports.
- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period.

The documents submitted pursuant to this condition do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Stratospheric Ozone Protection

C.21 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

D.1 FACILITY OPERATION CONDITIONS - Woodworking operations

Facility Description [326 IAC 2-7-5(15)]

Woodworking operations 014, with a maximum rating of 2,750 pounds per hour. Emissions shall be controlled by a baghouse, then exhausted at Stack/Vent ID#N.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Nonattainment Area Particulate Matter Emission Limitations [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2, particulate matter emissions from the woodworking operations shall not exceed 0.03 grains per dry standard cubic foot.

D.1.2 Opacity

The opacity from the woodworking operations shall not exceed 10% when vented to the atmosphere.

D.1.3 Baghouse limitations

Baghouse limitations: The baghouse does not exhaust to the atmosphere greater than one hundred twenty-five thousand (125,000) cubic feet of air per minute and shall not emit particulate matter with a diameter less than ten (10) microns in excess of three-thousandths (0.003) grain per dry standard cubic feet of outlet air.

D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Determination Requirements

D.1.5 Testing Requirements [326 IAC 2-7-6(1), (6)]

The Permittee is not required to test this facility by this permit. However, IDEM may require testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the PM limit specified in Condition D.1.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

D.1.6 Opacity

Compliance with the limitation in Condition D.1.2 shall be determined by 40 CFR 60, Appendix A, Method 9.

D.1.7 Particulate Matter (PM)

The baghouse for PM control shall be in operation at all times when the woodworking machinery is in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.8 Visible Emissions Notations

- (a) Daily visible emission notations of the woodworking baghouse stack exhaust shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.

- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

D.1.9 Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the woodworking operation when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting indoors. All defective bags shall be replaced.

D.1.10 Broken Bag or Failure Detection

In the event that bag failure has been observed:

- (a) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.11 Record Keeping Requirements

- (a) To document compliance with Condition D.1.8, the Permittee shall maintain records of daily visible emission notations of the woodworking baghouse stack exhaust.
- (b) To document compliance with Condition D.1.9, the Permittee shall maintain records of the results of the inspections required under Condition D.1.9 and the dates the vents are redirected.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.2 FACILITY OPERATION CONDITIONS - Surface Coating Booths

Facility Description [326 IAC 2-7-5(15)]

(a) The first line consisting of the following units:

Twelve (12) surface coating booths, identified as units 01-012, with dry filters for control. Unit 01 exhausts to stack A; Unit 02 exhausts to stack B; Unit 03 exhausts to stack C; Unit 04 exhausts to stack D; Unit 05 exhausts to stack E; Unit 06 exhausts to stack F; Unit 07 exhausts to stack G; Unit 08 exhausts to stack H; Unit 09 exhausts to stack I; Unit 010 exhausts to stack J; Unit 011 exhausts to stack K; and Unit 012 exhausts to stack L.

(b) The second line consisting of the following units:

- (a) One (1) SAP/NGR Booth, identified as 21/22, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filter and exhausting externally through stacks 2A and 2B.
- (b) One (1) wash Coat Booth, identified as 23, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filter and exhausting externally through stack 2C.
- (c) One (1) Stain Booth, identified as 25, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filters and exhausting externally through stack 2D.
- (d) One (1) Sealer Booth, identified as 27, with a maximum rated capacity of 30 units per hour, particulate emissions controlled by dry-filters and exhausting externally through stack 2F.
- (e) One (1) First Topcoat Booth with one (1) flash tunnel, identified as 29, with a maximum rated capacity of 30 units per hour. Particulate emissions from the First Topcoat Booth are controlled by dry-filters and exhausting externally through stack 2H. The flash tunnel exhausts externally through stack 2I.
- (f) One (1) Second Topcoat Booth with one (1) flash tunnel, identified as 30, with a maximum rated capacity of 30 units per hour. Particulate emissions from the Second Topcoat Booth are controlled by dry-filters and exhausting externally through stack 2J. The flash tunnel exhausts externally through stack 2K.
- (g) Two (2) Drying Ovens identified as 26 and 31, with a maximum rated capacity of 1.0 million Btu per hour each, and exhausting externally through stacks 2E and 2L.
- (h) One (1) Drying Oven identified as 28, with a maximum rated capacity of 4.0 million Btu per hour, and exhausting externally through stacks 2G-1, 2G-2, and 2G-3.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.2.1 General Provisions Relating to HAPs [326 IAC 20-1-1][40 CFR 63, Subpart A]

The provisions of 40 CFR 63, Subpart A - General Provisions, which are incorporated as 326 IAC 20-1-1, apply to the facility described in this section except when otherwise specified in 40 CFR 63, Subpart JJ.

D.2.2 PSD Minor Limit [326 IAC 2-2][40 CFR 63, Subpart A]

The source shall use less than 250 tons of VOC, including coatings, dilution solvents, and cleaning solvents per year. This usage limit is required to limit the potential to emit of VOC to less than 250 tons per twelve (12) consecutive month period. Compliance with this limit makes 326 IAC 2-2 (Prevention of Significant Deterioration) and 40 CFR 52.21 not applicable.

D.2.3 Nonattainment Particulate Matter Emission Limitations [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2, particulate matter emissions from both the first and second surface coating line shall not exceed 0.03 grains per dry standard cubic foot.

D.2.4 Volatile Organic Compounds (VOC) [326 IAC 8-2-12]

Pursuant to 326 IAC 8-2-12 (Wood Furniture and Cabinet Coating), with the exception of no more than ten (10) gallons of coating per day used for touch-up and repair operations, the surface coating applied to wood furniture shall utilize one of the following application methods:

- Airless Spray Application
- Air Assisted Airless Spray Application
- Electrostatic Spray Application
- Electrostatic Bell or Disc Application
- Heated Airless Spray Application
- Roller Coating
- Brush or Wipe Application
- Dip-and Drain Application

High Volume Low Pressure (HVLP) Spray Application is an accepted alternative method of application for Air Assisted Airless Spray Application. HVLP spray is the technology used to apply coating to substrate by means of coating application equipment which operates between one-tenth (0.1) and ten (10) pound per square inch gauge (psig) air pressure measured dynamically at the center of the air cap and at the air horns of the spray system.

D.2.5 Wood Furniture NESHAP [40 CFR 63, Subpart JJ]

- (a) The wood furniture coating operation is subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP), 326 IAC 20-14, (40 CFR 63, Subpart JJ), with a compliance date of December 7, 1998.
- (b) Pursuant to 40 CFR 63, Subpart JJ, the wood furniture coating operations shall comply with the following conditions:
 - (1) Limit the volatile hazardous air pollutant (VHAP) emissions from finishing operations as follows:
 - (A) Achieve a weighted average VHAP content across all coatings of 1.0 pound VHAP per pound solids; or
 - (B) Use compliant finishing materials in which all stains, washcoats, sealers, topcoats, basecoats and enamels have a maximum VHAP content of 1.0 pound VHAP per pound solid, as applied. Thinners used for on-site formulation of washcoats, basecoats, and enamels have a 3.0 percent maximum VHAP content by weight. All other thinners have a 10.0 percent maximum VHAP content by weight; or
 - (C) Use a control device to limit emissions; or
 - (D) Use a combination of (A), (B), and (C).

- (2) Limit VHAP emissions contact adhesives as follows:
 - (A) For foam adhesives used in products that meet the upholstered seating flammability requirements, the VHAP content shall not exceed 1.8 pounds VHAP per pound solids.
 - (B) For all other contact adhesives (except aerosols and contact adhesives applied to nonporous substrates) the VHAP content shall not exceed 1.0 pound VHAP per pound solid.
 - (C) Use a control device to limit emissions.
- (3) The strippable spray booth material shall have a maximum VOC content of 0.8 pounds VOC per pound solids.

D.2.6 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control device.

D.2.7 Work Practice Standards [40 CFR 63.803]

The owner or operator of an affected source subject to this subpart shall prepare and maintain a written work practice implementation plan within sixty (60) calendar days after the compliance date. The work practice implementation plan must define environmentally desirable work practices for each wood furniture manufacturing operation and at a minimum address each of the following work practice standards as defined under 40 CFR 63.803:

- (a) Operator training course.
- (b) Leak inspection and maintenance plan.
- (c) Cleaning and washoff solvent accounting system.
- (d) Chemical composition of cleaning and washoff solvents.
- (e) Spray booth cleaning.
- (f) Storage requirements.
- (g) Conventional air spray guns shall only be used under the circumstances defined under 40 CFR 63.803(h).
- (h) Line Cleaning.
- (i) Gun Cleaning.
- (j) Washoff operations.
- (k) Formulation assessment plan for finishing operations.

Compliance Determination Requirements

D.2.8 Testing Requirements [326 IAC 2-7-6(1),(6)] [40 CFR 63, Subpart JJ]

- (a) Pursuant to 40 CFR 63, subpart JJ, if the Permittee elects to demonstrate compliance using 63.804(a)(3) or 63.804(c)(2) or 63.804(d)(3) or 63.804(e)(2), performance testing must be conducted in accordance with 40 CFR 63, subpart JJ and 326 IAC 3-6.
- (b) IDEM may require compliance testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the limits specified in Conditions D.2.2, D.2.3 and D.2.5 shall be determined by performance tests conducted in accordance with Section C - Performance Testing.

D.2.9 Volatile Organic Compounds (VOC)

Compliance with VOC content limitations contained in Condition D.2.5 shall be determined pursuant to 326 IAC 8-1-4(a) and 326 IAC 8-1-2(a), using formulation data supplied by the coating manufacturer. The OAM reserves the authority to determine compliance using Method

24 in conjunction with the analytical procedure specified in 326 IAC 8-1-4.

D.2.10 VOC Emissions

Compliance with Condition D.2.2 shall be demonstrated within 30 days of the end of each month based on the total volatile organic compound usage for the most recent twelve (12) consecutive month period

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.2.11 Particulate Matter (PM)

The dry filters for PM overspray control shall be in operation at all times when the twelve (12) surface coating booths are in operation.

D.2.12 Monitoring

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating booth stacks while one or more of the booths are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.2.13 Record Keeping Requirements

- (a) To document compliance with Condition D.2.2 the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be complete and sufficient to establish compliance with the VHAP usage limits established in Condition D.2.2.
 - (1) The amount and VOC content of each coating material and solvent used. Records shall include purchases orders, invoices and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) A log of the dates of use;
 - (3) The cleanup solvent usage for each month;
 - (4) The total VOC usage for each month;
 - (5) The weight of VOC's emitted for each compliance period.

- (b) To document compliance with Condition D.2.5 the Permittee shall maintain records in accordance with (1) through (5) below. Records maintained for (1) through (5) shall be complete and sufficient to establish compliance with the VHAP usage limits established in Condition D.2.5.
 - (1) Certified Product Data Sheet for each finishing material, thinner, contact adhesive and strippable booth coating.
 - (2) The VHAP content in pounds of VHAP per pounds of solids, as applied, for all finishing materials and contact adhesives used.
 - (3) The VOC content in pounds of VOC per pounds of solids, as applied, for each strippable coating used.
 - (4) The VHAP content in weight percent of each thinner used.
 - (5) When the averaging compliance method is used, copies of the averaging calculations for each month as well as the data on the quantity of coating and thinners used to calculate the average.
- (c) To document compliance with Condition D.2.7, the Permittee shall maintain records demonstrating actions have been taken to fulfill the Work Practice Implementation Plan.
- (d) To document compliance with Conditions D.2.11 and D.2.12, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections and those additional inspections prescribed by the Preventive Maintenance Plan.
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.2.14 Reporting Requirements

- (a) A quarterly summary of the information to document compliance with Condition D.2.2 shall be submitted to the address listed in Section C – General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being used.
- (b) An Initial Compliance Report to document compliance with Condition D.2.5, and the Certification form shall be submitted within sixty (60) calendar days following the compliance date of December 7, 1998. The initial compliance report must include data from the entire month that the compliance data falls.
- (c) A semi-annual Continuous Compliance Report to document compliance with Condition D.2.5, and the Certification form shall be submitted within thirty (30) days after the end of the six (6) months being reported.

The six (6) month periods shall cover the following months:

- (1) January 1 through June 30.
- (2) July 1 through December 31.
- (d) The reports required in (a) and (b) of this condition shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management

Inwood Office Furniture Co., Inc.
Jasper, Indiana
Permit Reviewer: Karen Purtell

First Administrative Amend. 037-12407
Modified by: David Howard

Page 36 of 42
T037-12168-00012

100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

D.3 FACILITY OPERATION CONDITIONS - Boiler

Facility Description [326 IAC 2-7-5(15)]

One (1) natural gas boiler 013, with a maximum rating of 2.6 million Btu per hour. Emissions shall be exhausted at stack M.

One (1) Air Makeup Unit utilized for general building ventilation, identified 33, with a maximum rated capacity of 2.10 million Btu per hour, and exhausting externally.

Seven (7) Air Makeup Units, two (2) integrated with the SAP/NGR Booth and One (1) integrated with each of the other five (5) surface coating booths, with a maximum rated capacity of 1.5 million Btu per hour per unit, and exhausting internally into the booth.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.3.1 Nonattainment Area Particulate Matter Emission Limitations [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2, particulate matter emissions from the natural gas boiler shall not exceed 0.03 grains per dry standard cubic foot.

Compliance Determination Requirements

D.3.2 Testing Requirements [326 IAC 2-7-6(1), (6)]

The Permittee is not required to test this facility by this permit. However, IDEM may require testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the PM limit specified in Condition D.3.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

D.4 FACILITY OPERATION CONDITIONS – Final Touchup Sanding Operation

Facility Description [326 IAC 2-7-5(15)]

One (1) Final Touchup Sanding Booth, identified as 32, with a maximum rated capacity of 7.5 tons of wood per hour, particulate emissions controlled by cartridge-filters and exhausting internally.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.4.1 Nonattainment Area Particulate Matter Emission Limitations [326 IAC 6-1-2]

Pursuant to 326 IAC 6-1-2, particulate matter emission limitations from the final touchup sanding booth operation shall not exceed 0.03 grains per dry standard cubic foot.

D.4.2 Opacity

The opacity from the sanding operation shall not exceed 40% when vented to the atmosphere.

D.4.3 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Determination Requirements

D.4.4 Testing Requirements [326 IAC 2-7-6(1), (6)]

The Permittee is not required to test this facility by this permit. However, IDEM may require testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the PM limit specified in Condition D.1.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

D.4.5 Particulate Matter (PM)

The cartridge filter for PM control shall be in operation at all times when the final touchup sanding booth is in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.4.6 Visible Emissions Notations

- (a) Daily visible emission notations of the cartridge filter stack exhaust shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.

- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

D.4.7 Parametric Monitoring

The Permittee shall record the total static pressure drop across the cartridge filters used in conjunction with the final touchup sanding operation, at least once weekly when the final touchup sanding operation is in operation when venting to the atmosphere. Unless operated under conditions for which the Compliance Response Plan specifies otherwise, the pressure drop across the cartridge filters shall be maintained within the range of 2.0 to 8.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAM and shall be calibrated at least once every six (6) months.

D.4.8 Cartridge Filter Inspections

An inspection shall be performed each calendar quarter of all cartridge filters controlling the final touchup sanding operation when venting to the atmosphere. A cartridge filter inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting indoors. All defective cartridge filters shall be replaced.

D.4.9 Broken Cartridge Filter or Failure Detection

In the event that bag failure has been observed:

- (a) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment cartridge filters, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.4.10 Record Keeping Requirements

- (a) To document compliance with Condition D.4.6, the Permittee shall maintain records of daily visible emission notations of the final touchup sanding stack exhaust when venting to the atmosphere.
- (b) To document compliance with Condition D.4.8, the Permittee shall maintain records of the results of the inspections required under Condition D.4.8 and the dates the vents are redirected when venting to the atmosphere.

- (c) To document compliance with Condition D.4.7, the Permittee shall maintain the following:
 - (1) Daily records of the following operational parameters during normal operation when venting to the atmosphere:
 - (A) Inlet and outlet differential static pressure; and
 - (B) Cleaning cycle: frequency and differential pressure
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
CERTIFICATION**

Source Name: Inwood Office Furniture Co., Inc.
Source Address: 1108 E. 15th Street, Jasper, Indiana 47546
Mailing Address: P.O. Box 646, Jasper, Indiana 47547-0646
Part 70 Permit No.: T037-6048-00012

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Test Result (specify)
- 9 Report (specify)
- 9 Notification (specify)
- 9 Other (specify)

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION
P.O. Box 6015
100 North Senate Avenue
Indianapolis, Indiana 46206-6015
Phone: 317-233-5674
Fax: 317-233-5967**

**PART 70 OPERATING PERMIT
EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: Inwood Office Furniture Co., Inc.
Source Address: 1108 E. 15th Street, Jasper, Indiana 47546
Mailing Address: P.O. Box 646, Jasper, Indiana 47547-0646
Part 70 Permit No.: T037-6048-00012

This form consists of 2 pages

Page 1 of 2

Check either No. 1 or No.2	
<input checked="" type="radio"/>	1. This is an emergency as defined in 326 IAC 2-7-1(12) C The Permittee must notify the Office of Air Management (OAM), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and C The Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16
<input checked="" type="radio"/>	2. This is a deviation, reportable per 326 IAC 2-7-5(3)(c) C The Permittee must submit notice in writing within ten (10) calendar days

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency/Deviation:
Describe the cause of the Emergency/Deviation:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency/Deviation started:
Date/Time Emergency/Deviation was corrected:
Was the facility being properly operated at the time of the emergency/deviation? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency/deviation:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by:
Title / Position:
Date:
Phone:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
Semi-Annual Report**

VOC and VHAP usage - Wood Furniture NESHAP

Source Name: Inwood Office Furniture Co., Inc.
Source Address: 1108 E. 15th Street, Jasper, Indiana 47546
Mailing Address: P.O. Box 646, Jasper, Indiana 47547-0646
Part 70 Permit No.: T037-6048-00012
Facility: Surface Coating
Parameter: VOC and VHAPs - NESHAP
Limit:
(1) Finishing operations -1.0 lb VHAP/lb Solids
(2) Thinners used for on-site formulation of washcoats, basecoats and enamels - 3% VHAP content by weight
(3) All other thinners - 10% VHAP content by weight
(4) Foam adhesives meeting the upholstered seating flammability requirements - 1.8 lb VHAP/lb Solids
(5) All other contact adhesives - 1.0 lb VHAP/lb Solids
(6) Strippable spray booth material - 0.8 pounds VOC per pound solids

YEAR: _____

Month	Finishing Operations (lb VHAP/lb Solid)	Thinners used for on-site formulation (% by weight)	All other thinners (% by weight)	Foam adhesives (upholstered) (lb VHAP/lb Solid)	Contact adhesives (lb VHAP/lb Solid)	Strippable spray booth material (lb VOC/lb Solid)
1						
2						
3						
4						
5						
6						

9 No deviation occurred in this six month period.

9 Deviation/s occurred in this six month period.

Deviation has been reported on: _____

Submitted by: _____
Title/Position: _____
Signature: _____
Date: _____
Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

Part 70 Quarterly Report

Source Name: Inwood Office Furniture Co., Inc.
Source Address: 1108 E. 15th Street, Jasper Indiana 47547
Mailing Address: P.O. Box 646, Jasper, Indiana 47547-0646
Part 70 Permit No.: T037-6048-00012
Facility: Surface Coating Operations
Parameter: VOC
Limit: less than 250 tons per twelve (12) consecutive month period

YEAR:

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

9 No deviation occurred in this quarter.

9 Deviation/s occurred in this quarter.
Deviation has been reported on:

Submitted by:

Title / Position:

Signature:

Date:

Phone:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**PART 70 OPERATING PERMIT
QUARTERLY COMPLIANCE MONITORING REPORT**

Source Name: Inwood Office Furniture Co., Inc.
Source Address: 1108 E. 15th Street, Jasper, Indiana 47546
Mailing Address: P.O. Box 646, Jasper, Indiana 47547-0646
Part 70 Permit No.: T037-6048-00012

Months: _____ **to** _____ **Year:** _____

This report is an affirmation that the source has met all the compliance monitoring requirements stated in this permit. This report shall be submitted quarterly. Any deviation from the compliance monitoring requirements and the date(s) of each deviation must be reported. Additional pages may be attached if necessary. This form can be supplemented by attaching the Emergency/Deviation Occurrence Report. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD		
9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD:		
Compliance Monitoring Requirement (eg. Permit Condition D.1.3)	Number of Deviations	Date of each Deviations

Form Completed By:
Title/Position:
Date:
Phone:

Attach a signed certification to complete this report.